

'Braid' series



Applications

- Removing obstinate rust
- Cleaning metal surfaces
- Removing attachments, paint

Braid Disc



Braid Wheel with shaft



Braid Wheel with hole



- A special type of nonwoven nylon abrasive material is sintered to make the super-strong and flexible material used in the products.
- Best suited to tasks that involve the cleaning of surfaces alone without grinding the substrate.

Braid Disc

item no.	dia x thickness x hole(mm)	max RPM/adequate RPM	grit	Q'ty/box
BRD10016	100 x 13 x 16	12,000r.p.m./6,000r.p.m.	36	5



Braid Wheel with shaft

item no.	dia x thickness x hole(mm)	max RPM/adequate RPM	grit	Q'ty/box
BRW5013	50 x 13 x 6	16,000r.p.m./12,000r.p.m.	36	10
BRW5026	50 x 26 x 6	16,000r.p.m./12,000r.p.m.	36	10



Braid Wheel with hole

item no.	dia x thickness x hole(mm)	max RPM/adequate RPM	grit	Q'ty/box
BRW5013	50 x 13 x 6	16,000r.p.m./12,000r.p.m.	36	10
BRW7513	75 x 13 x 6	10,500r.p.m. / 8,000r.p.m.	36	10
BRW10013	100 x 13 x 13	8,000r.p.m. / 6,000r.p.m.	36	10



Braid Wheel attachment



●L (for 100mm dia.)



●S (for 50mm/75mm dia.)