

'Poli Light' series



Applications

- Substrate treatment for a mirror finish
- Removing oxide films, stains
- Blurring scratch marks on aluminum, copper
- Smoothing nappy wood surfaces

Poli Light Disc S Poli Light Wheel

Poli Light Wheel

Poli Light Wheel T



- The use of nonwoven fabric made of special fiber prevents welding to the work piece.
 - Best suited to surface roughness adjustment and other processes prior to glazing, painting and laminating
- ☆ Products of the "Poli Light" series are adapted to be used in dry conditions. They can also be used in wet polishing tasks with oil-based grinding fluids (water-insoluble grinding fluids) and grease-based abrasives. Under no circumstances, however, should they be used with water or water-soluble grinding fluids.

Poli Light Disc S

item no.	dia x thickness x hole (mm)	RPM	grit														Q'ty/box		
			24	36	40	60	80	100	120	150	180	240	320	400	600	800		1000	0
PLD10016S	100 x 10 x 16	13,000r.p.m.				●	●			●	●			●	●			●	5

Poli Light Wheel

item no.	dia x width x hole (mm)	RPM	grit														Q'ty/box		
			24	36	40	60	80	100	120	150	180	240	320	400	600	800		1000	0
PLW3025	30 x 25 x 6 x 40	12,000r.p.m.				●	●			●	●			●	●			●	5
PLW4025	40 x 25 x 6 x 40	12,000r.p.m.				●	●			●	●			●	●			●	5
PLW5025	50 x 25 x 6 x 40	10,000r.p.m.				●	●			●	●			●	●			●	5
PLW6025	60 x 25 x 6 x 40	10,000r.p.m.				●	●			●	●			●	●			●	5
PLW8025	80 x 25 x 6 x 40	8,000r.p.m.				●	●			●	●			●	●			●	5

Poli Light Wheel T

item no.	dia x layer x shaft dia x shaft length(mm)	RPM	grit														Q'ty/box		
			24	36	40	60	80	100	120	150	180	240	320	400	600	800		1000	0
PLWT103P4P3	10 x 3P/4P x 3 x 35	12,000r.p.m.				●	●			●	●			●	●			●	10
PLWT153P4P3	15 x 3P/4P x 3 x 35	12,000r.p.m.				●	●			●	●			●	●			●	10
PLWT203P4P3	20 x 3P/4P x 3 x 35	12,000r.p.m.				●	●			●	●			●	●			●	10
PLWT253P4P3	25 x 3P/4P x 3 x 35	12,000r.p.m.				●	●			●	●			●	●			●	10
PLWT303P4P3	30 x 3P/4P x 3 x 35	12,000r.p.m.				●	●			●	●			●	●			●	10

☆ grit#60-#240 3ply, grit#400-#1000 4ply