

# Felt products



## Application

- Polishing stainless steel, brass, aluminum, precious metals
- Mirror finishing (Mirror finishing requires the use of an oil-based buffing cake.)

## Felt Disc

### Felt Disc S



### Felt Disc H



- Available in the soft type (S) and hard type (H) variants.
- The S products are suited to soft materials, whereas the H products are recommended for thick metal plates and stainless steel work pieces.

## Felt Wheel with shaft



- Choose straight or cannonball-shaped (hodan) felt wheels according to the shape of the work piece

## Sisal HG Buff Disc



- The structure, designed to suppress burn marks from the heat of rotation, is best suited to substrate polishing.

## Felt Wheel



- Holed wheels, which have broad applications, should be fit on a dedicated arbor.

## Aobou/Shirobou (oil based buffing cake)



- **Aobou(GB)**  
100x40x20(mm) 180g  
For finishing stainless steel, aluminum and chrome coating



- **Shirobou(WB)**  
100x40x20(mm) 140g  
For finishing brass, tin and noble metal

## Felt Disc S,H



item no.	dia x thickness x hole(mm)	type	RPM	Q'ty/ box
FUD10016S	100 x 12 x 16	S(soft type)	13,000r.p.m.	5
FUD10016H	100 x 12 x 16	H(hard type)	13,000r.p.m.	5

## Felt Wheel with shaft(straight)



item no.	dia x width x shaft dia x shaft length(mm)	RPM	Q'ty/ box
FUS612H	6 x 12 x 3 x 35	20,000r.p.m.	10
FUS1015H	10 x 15 x 3 x 35	20,000r.p.m.	10
FUS1520H	15 x 20 x 6 x 30	15,000r.p.m.	10
FUS2025H	20 x 25 x 6 x 30	15,000r.p.m.	10

## Felt Wheel with shaft(hodan)



item no.	dia x width x shaft dia x shaft length(mm)	RPM	Q'ty/ box
FUM612H	6 x 12 x 3 x 35	20,000r.p.m.	10
FUM1015H	10 x 15 x 3 x 35	20,000r.p.m.	10
FUM1520H	15 x 20 x 6 x 30	15,000r.p.m.	10
FUM2025H	20 x 25 x 6 x 30	15,000r.p.m.	10

## Sisal HG Buff Disc



item no.	dia x hole(mm)	RPM	Q'ty/ box
SHGB9016	90 x 16	13,000r.p.m.	5

## Felt Wheel



item no.	dia x thickness x hole(mm)	attachment size	RPM	Q'ty/ box
FUW5006S	50 x 12 x 6	S (for 50mm dia.)	12,000r.p.m.	10
FUW7510S	75 x 12 x 10	M (for 75mm dia.)	9,000r.p.m.	10
FUW10015S	100 x 15 x 15	L (for 100mm dia.)	6,000r.p.m.	5

## Felt Wheel attachment



●L (for 100mm dia.) shaft dia. 6mm



●M (for 75mm dia.) shaft dia. 6mm



●S (for 50mm dia.) shaft dia. 6mm